



Pöördlaserid



	ECO 600 HV	PRIMUS ² HV	PRIMUS ² H2N
Täpsus	1 mm/ 10 m	0.5 mm/ 10 m	0.5 mm/ 10 m
Kompensaator	± 5°	± 5°	± 5°
Tööulatus	~ 300 m	~ 300 m	~ 400 m
Laser	< 5 mW, 3R	< 5 mW, 3R	< 5 mW, 3R
Skaneerimine	0°, 6°, 20°, 50°, 90°	0°, 5°, 10°, 15°	-
Pöörlemiskiirus	0,60,120,300,600 p/m	10,60,300,600 p/m	600 p/m
Aku / kestvus	3800 mAh / 30 tundi	100 tundi	100 tundi
Kaldenurk	käsitsi	käsitsi	± 10%
Tolmukindlus	IP5 (tavatolm)	IP6 (peentolm)	IP6 (peentolm)
Vihmakindlus	IPX4 (pritsmed)	IPX6 (vee kallamine)	IPX6 (vee kallamine)
Töötemperatuur	-20°C...+50°C	-20°C...+50°C	-20°C...+50°C
Kukkumiskindlus	-	1 m	1 m
Garantii	1 a	3 a	3 a

Komplekti kuuluvad: pöördlaser, pult, vastuvõtja, latt, kandekast.

